

LAW OFFICES  
**SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC**  
2100 PENNSYLVANIA AVENUE, N.W.  
WASHINGTON, DC 20037-3213  
TELEPHONE (202) 293-7060  
FACSIMILE (202) 293-7860  
www.sughrue.com

November 2, 2000

## BOX PCT

Assistant Commissioner for Patents  
Washington, D.C. 20231

PCT/FR99/01083 ✓  
-filed May 7, 1999 ✓

Re: Application of Vojin JEREMIJEVIC  
DEVICE FOR PROTECTING AND NEUTRALIZING A NEEDLE FOR  
MEDICAL USE ✓  
Our Ref: Q61622

Dear Sir:

The following documents and fees are submitted herewith in connection with the above application for the purpose of entering the National stage under 35 U.S.C. § 371 and in accordance with Chapter II of the Patent Cooperation Treaty:

- ☒ an executed Declaration and Power of Attorney.
- ☒ an English translation of the International Application.
- ☒ 7 sheet(s) of formal drawings.
- ☒ verified Statement claiming Small Entity Status - Small Business Concern
- ☒ an executed Assignment and PTO 1595 form.
- ☒ a Preliminary Amendment

It is assumed that copies of the International Application, the International Search Report and cited references, the International Preliminary Examination Report, and any Articles 19 and 34 amendments as required by § 371(c) will be supplied directly by the International Bureau, but if further copies are needed, the undersigned can easily provide them upon request.

Priority is claimed from May 15, 1998, December 30, 1998, and February 4, 1999, based on French Application Nos. 98/06277, 98/16701, and 99/01284, respectively.

### A Preliminary Amendment is enclosed.

The Government filing fee is calculated as follows (Small Entity fees apply):

Total claims	25	-	20	=	5	x	\$9.00	=	\$45.00
Independent claims	2	-	3	=		x	\$40.00	=	\$80.00
Base Fee									\$430.00

### TOTAL FILING FEE

### Recordation of Assignment

### TOTAL FEE

**\$475.00**

**\$ 40.00**

**\$515.00**

SUGHRUE, MION, ZINN, MACPEAK &amp; SEAS, PLLC


Assistant Commissioner  
for Patents

Page 2

09/674643

Checks for the statutory filing fee of \$475.00 and Assignment recordation fee of \$40.00 are attached. You are also directed and authorized to charge or credit any difference or overpayment to said Account. The Commissioner is hereby authorized to charge any fees under 37 C.F.R. §§ 1.16, 1.17 and 1.492 which may be required during the entire pendency of the application to Deposit Account No. 19-4880. A duplicate copy of this transmittal letter is attached.

Respectfully submitted,



Robert J. Seas, Jr.

Registration No. 21,092

for

Neil B. Siegel, Reg. No. 25,200

SUGHRUE, MION, ZINN,  
MACPEAK & SEAS, PLLC  
2100 Pennsylvania Avenue, N.W.  
Washington, D.C. 20037-3213  
Telephone: (202) 293-7060  
Facsimile: (202) 293-7860

Date: November 2, 2000

09/674643

PATENT APPLICATION  
Attorney Docket No. Q61622

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of

Vojin JEREMIJEVIC

PCT/FR99/01083

-filed May 7, 1999

Filed: November 2, 2000

For: DEVICE FOR PROTECTING AND NEUTRALIZING A NEEDLE FOR MEDICAL USE

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

Prior to examination, please amend the above-identified application as follows:

**IN THE CLAIMS:**

**Please cancel claims 4-14 without prejudice or disclaimer.**

Please amend claims 1-3 and 15-25 as follows:

1. (Amended) A device for protecting [and neutralizing] a needle [(1, 201)] for medical use or the like, the needle having a sharp end [(2, 202)] and a base end [(3, 203), the device being characterized by the fact that it comprises], and able to take at least three positions, respectively a "starting position", a "in-use position" and a "locked position", comprising:

a sleeve [(10, 204)] having a through bore [(11, 205)] defined on a given axis [(12, 208)], said through bore being of a section that is not less than that of the needle to be protected;

[at least one] a first link [(13, 113, 14, 114)] having first and second ends [(15, 115, 16, 116, 17, 117, 18, 118)], said link being of a length "L<sub>1</sub>" defined between said two ends;

first resilient return hinge means [(19, 20)] for connecting the first end [(15, 16)] of the first link to the sleeve [(10)], said first hinge means being organized so that said first link takes

up a defined equilibrium position on a direction that makes an acute angle [(a)] ( $\alpha$ ) with the axis of the through bore;

base means [(21, 209)] suitable for receiving the base end [(3, 203)] of the needle to be protected [(1, 201)];

[at least one] a first crank arm [(22, 122, 23, 123)], said first crank arm being defined between first and second ends [(24, 124, 25, 125 - 26, 126, 27, 127)], said crank arm being of a length "I<sub>1</sub>" defined between its two ends, the length "I<sub>1</sub>" of the first crank arm being no greater than the length "L<sub>1</sub>" of the first link; and

first means [(28, 128, 29, 129, 30, 130, 31, 131)] for mounting each of said first and second ends of the first crank arm to pivot freely respectively on the second end [(17, 18)] of the first link and on the base means [(21, 209)].

2. (Amended) A device according to claim 1, [characterized by the fact that it] further [includes] including strut means [(40)] connecting said link [(13, 14)] to said crank arm [(22, 23)] when they are in a first [given] position, said strut means including a weak point [(41)] making it possible, on application of a given force, to break said strut means at said weak point.

3. (Amended) A device according to claim 1 [or 2], [characterized by the fact that it] further [includes snap-fastening means (50) to lock said link and said crank arm relative to each other in a second given position (Figure 5)] including:

a second link having first and second ends, said second link being of a length "L<sub>2</sub>" defined between said two ends;

second resilient return hinge means for connecting the first end of the second link to the sleeve, said second hinge means being organized so that said second link takes up a defined equilibrium position on a direction that makes an acute angle ( $\alpha'$ ) with the axis of the through bore;

a second crank arm, said second crank arm being defined between first and second ends, said second crank arm being of a length " $l_2$ " defined between its two ends, the length " $l_2$ " of the second crank arm being no greater than the length " $l_2$ " of the second link; and

second means for mounting each of said first and second ends of the second crank arm to pivot freely respectively on the second end of the second link and on the base means.

15. (Amended) A device for protecting and neutralizing a needle [(1, 201)] for medical use or the like [according to any one of claims 1 to 14,] the needle having a sharp end [(2, 202)] and a base end [(203)], the device comprising:

a sleeve [(204)] having a through bore [(205)], said through bore having first and second outlets [(206, 207)], said through bore being defined on a given axis [(208)] and having a cross-section that is not less than that of the needle [(201)], the needle being suitable for sliding through said bore;

a base [(209)] secured to the base end [(203)] of the needle [(201)]; and

resilient link means [(210)] connecting the sleeve [(204)] to the base [(209)], said resilient link means enabling the sleeve [(204)] to slide along the needle [(201)], the needle passing through the bore [(205)] of the sleeve via the first outlet [(206)] thereof, said sleeve being suitable for taking up two extreme positions;

[\*] a first position in which the sleeve surrounds the sharp end [(202)] of the needle, said sharp end being situated at a given distance from the second outlet [(207)] of the through bore [(205)]; and

[\*] a second position in which the face [(211)] of the sleeve [(204)] that includes the first outlet [(206)] of the through bore is positioned adjacent to the base [(209)];

[the device being characterized by the fact] wherein that it further comprises:

a first channel portion [(212)] made in the sleeve [(204)] and intersecting the through bore [(205)] in its portion lying between its second outlet [(207)] and the sharp end [(202)] of the needle [(201)] when the sleeve [(204)] is in its first position;

a shutter [(213)] slidably mounted in the first channel portion [(212)], said shutter being suitable for taking up a first position and a second position, the first position being one in which it is not situated in the through bore [(205)], and the second position being one in which it is situated in the through bore; and

means [(220)] for applying thrust on said shutter [(213)] when the sleeve [(204)] comes close to the base [(209)] on passing from its first position to its second position.

16. (Amended) A device according to claim 15, [characterized by the fact that] wherein the means [(220)] for applying thrust on said shutter when the sleeve comes close to the base on passing from its first position to its second position are constituted by:

a second channel portion [(221)] made in the sleeve [(204)] in continuity with the first channel portion [(212)] and opening out via an outlet orifice [(222)] in the same face [(211)] of the sleeve as has the first outlet [(206)] of the through bore [(205)];

a flexible rod [(223)] preformed into an arcuate bow shape and slidably mounted in said second channel portion [(221)] in such a manner that a first end [(224)] thereof is associated with the shutter [(213)], and a second end [(225)] thereof emerges from the outlet orifice [(222)] of the second channel portion by an amount that is not less than the distance the shutter [(213)] needs to travel in order to pass from its first position to its second position; and

a release cavity [(226)] adjacent the second channel portion [(221)] and in communication with said second channel portion, the release cavity being designed so that, when the shutter [(213)] is held in its first position, the flexible rod [(223)] can deform in bending to penetrate laterally into said release cavity [(226)] when the face [(211)] of the sleeve having the first outlet [(206)] of the through bore [(205)] comes close to the base [(209)].

17. (Amended) A device according to claim 16, [characterized by the fact that it] further [includes] including means [(227)] for locking the position of the second end [(225)] of the flexible rod [(223)] when said rod is caused to enter into the second channel portion [(221)].

18. (Amended) A device according to claim 17, [characterized by the fact that] wherein the means [(227)] for locking the position of the second end [(225)] of the flexible rod [(223)] when it is retracted into the second channel portion [(221)] are] is constituted by at least one barb [(228)] secured to the flexible rod [(223)] and a housing [(229)] complementary to the barb [(228)] formed in the wall of the second channel portion [221]].

19. (Amended) A device according to [any one of claims 15 to 18] claim 15, [characterized by the fact that] wherein the first channel portion [(212)] has at least a first part [(231)] and a second

part [(232)] formed on either side of the through bore [(205)], the first part [(231)] of the first channel portion being in line with the second channel portion [(221)], the shutter [(213)] being contained completely within said first part [(231)] of the first channel portion [(212)] when it is in its first position, and by the fact that the device further includes a substantially U-shaped fork [(233)] secured to the shutter [(213)], the two limbs [(234, 235)] of the fork being spaced apart from each other by a distance of not less than the diameter of the needle [(201)], said fork [(233)] being shaped in such a manner that[,] when the shutter [(213)] is in its first position, the [gap (236)] space defined between the two limbs [(234, 235)] thereof is situated on the axis [(208)] of the through bore [(205)] and the two limbs [(234, 235)] extend at least in part into the second part [(232)] of the first channel portion [(212)].

20. (Amended) A device according to claim 19, [characterized by the fact that] wherein the flexible rod [(223)], the shutter [(213)], and the fork [(233)] are made as a single piece.

21. (Amended) A device according to claim 20, [characterized by the fact that] wherein said piece is made of plastics material by molding.

22. (Amended) A device according to [any one of claims 16 to 21] claim 16, [characterized by the fact that] wherein the two channel portions [(212, 221)] are contained in a plane [(240)] that also contains the axis [(208)] of the through bore [(205)], the sleeve [(204)] being made as two half-shells [(241, 242)] organized to be assembled together about said plane [(40)] containing the two channel portions [(212, 221)].



23. (Amended) A device according to [any one of previous claims, characterized by the fact that] claim 1, wherein the base means [(21, 209)] comprises two first and second rings [(301-302, 311-312)], the first ring [(301, 331)] receiving the low end [(3, 203)] of the needle, and means [(320)] for connecting said two rings between them by weak points.

24. (Amended) A device according to claim 23, [characterized by the fact that] wherein each of the two rings comprises an opening [(321, 322)], the two openings being realized to form, when the two rings are connected between them, the female part of a male-female jointing able to cooperate with the complementary male part constituted by an end-part [(323)] of a syringe [(325)], the total depth of these two openings, when the two rings are connected between them, being lower than the height of the end-part of the syringe.

25. (Amended) A device according to [any one of claims 23 and 24, characterized by the fact that it] claim 23, further [includes] including a not-withdrawal ring [(330)] located on the wall [(331)] of said second ring.

**Please add new claims 26-36 as follows:**

--26. A device according to claim 3, wherein the lengths "L<sub>1</sub>" and "L<sub>2</sub>" are substantially equal to common value "L" and that the lengths "I<sub>1</sub>" and "I<sub>2</sub>" are substantially equal to a common value "I".--

--27. A device according to claim 3, wherein the first and second links and the first and second crank arms are situated substantially in a common plane and form substantially a quadrilateral

whose diagonals are substantially perpendicular, the diagonal interconnecting the vertices of the quadrilateral situated respectively at the sleeve and at the base means coinciding substantially with the axis of the through bore.--

--28. A device according to claim 1, wherein at least two of the following elements are made of the same material: sleeve; base means; link; crank arm; hinge means; and freely pivoting mounting means.--

--29. A device according to claim 28, wherein said at least two elements are made by molding.--

--30. A device according to claim 29, wherein the material is a plastics material.--

--31. A device according to claim 1, wherein the length " $L_1$ " of the link and the length " $I_1$ " of the crank arm are determined in such a manner than the sum  $L_1 + I_1$  and the sum  $L_1 + I_1 + M$ , where " $M$ " represents the length of the sleeve, bracket the length " $A$ " of the needle to be protected as measured between its sharp end and its base end.--

--32. A device according to claim 3, further including a casing made of a resilient material surrounding under tension the assembly constituted by the sleeve, the first and second links, the first and second hinge means, the first and second crank arms, the first and second means for mounting the first and second ends of the first and second crank arms to pivot respectively on the

second ends of the first and second links and on the base means, and at least a portion of the base means.--

--33. A device according to claim 32, wherein the resilient material from which the casing is made is transparent.--

--34. A device according to claim 32, further including a sachet made of a non-stretch material, the sachet containing a given substance and being capable of tearing under a given traction, and means for securing the sachet and the casing substantially at two opposite points of the inside wall of the casing, the two said points being situated substantially facing the first means for mounting the first ends of the first and second crank arms to pivot freely on the second ends of the first and second links.--


--35. A device according to claim 34, wherein the substance contained in the sachet presents at least one of the following properties: being suitable for absorbing at least a portion of visible light, being suitable for hardening, being suitable for sterilizing.--

--36. A device according to claim 1, further including, for neutralizing said needle, snap-fastening means to lock said link and said crank arm relative to each other in a second given position.--

**REMARKS**

The amendments to the claims are made to remove the multiple dependencies, improve readability and conform to U.S. practice. No new matter is added by any of the above amendments. Entry and consideration of this Amendment is respectfully requested.

Respectfully submitted,



Robert J. Seas, Jr.  
Registration No. 21,092

for

Neil B. Siegel, Reg. No. 25,200

SUGHRUE, MION, ZINN,  
MACPEAK & SEAS, PLLC  
2100 Pennsylvania Avenue, N.W.  
Washington, D.C. 20037-3213  
Telephone: (202) 293-7060  
Facsimile: (202) 293-7860

Date: November 2, 2000

Applicant or Patentee: Vojin JEREMIJEVIC  
Serial or Patent No.: \_\_\_\_\_  
Filed or Issued: \_\_\_\_\_  
Title: Device for Protecting and Neutralizing a Needle for Medical Use

Attorney's  
Docket No.: Q61622

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS  
(37 CFR 1.9(f) & 1.27(c))--SMALL BUSINESS CONCERN

I hereby declare that I am

- ☐ the owner of the small business concern identified below:  
☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF SMALL BUSINESS CONCERN DEVICE RESEARCH & DEVELOPMENT (DRD)

ADDRESS OF SMALL BUSINESS CONCERN 5, rue Emile Bian  
1235 LUXEMBOURG (LUXEMBOURG)

I hereby declare that the above identified small business concern qualifies as a small business concern as defined in 13 CFR 121.12, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees to the United States Patent and Trademark Office, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention, entitled "Device for protecting and neutralizing a needle for medical use" by inventor Vojin JEREMIJEVIC described in

- ☒ the specification filed herewith  
☐ application serial no. \_\_\_\_\_, filed \_\_\_\_\_  
☐ patent no. \_\_\_\_\_, issued \_\_\_\_\_

If the rights held by the above identified small business concern are not exclusive, each individual, concern or organization having rights in the invention is listed below\* and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e). \*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

NAME \_\_\_\_\_  
ADDRESS \_\_\_\_\_  
☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

NAME \_\_\_\_\_  
ADDRESS \_\_\_\_\_  
☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING PATRICK ROCHAS - Stéphan LIEGERS  
TITLE OF PERSON IF OTHER THAN OWNER DIRECTOR DIRECTOR  
ADDRESS OF PERSON SIGNING 5, rue Emile Bian L. 1235 LUXEMBOURG

SIGNATURE [Signature] DATE 26 October 2000

71PRTS

09/ 674 643

526 Rec'd PAT. 02 NOV 2000

1

DEVICE FOR PROTECTING AND NEUTRALIZING A NEEDLE  
FOR MEDICAL USE

5 The present invention relates devices for protecting and neutralizing  
needles that have a sharp end and a base end, which have a particularly  
advantageous application lying specifically in protecting and neutralizing the  
needles of syringes, and more particularly devices for protecting and  
neutralizing needles that are intended for use by professionals in the medical  
field or the like.

10 Needle protection and neutralization devices already exist, but they are  
generally relatively complex and expensive, which limits their use.

Thus, a particular object of the present invention is to provide a device  
for protecting and neutralizing a needle for medical use or the like which  
greatly mitigates the drawbacks of prior art devices.

15 More precisely, the present invention provides a device for protecting  
and neutralizing a needle for medical use or the like, the needle having a  
sharp end and a base end, the device being characterized by the fact that it  
comprises:

20 a sleeve having a through bore defined on a given axis, said through  
bore being of a section that is not less than that of the needle to be protected;

at least one first link having first and second ends, said first link being  
of a defined length "L<sub>1</sub>" between its two ends;

25 first resilient return hinge means for connecting the first end of the first  
link to the sleeve, said first hinge means being organized so that said first link  
takes up a defined equilibrium position on a direction that makes an acute  
angle with the axis of the through bore;

base means suitable for receiving the base end of the needle;

25 at least one first crank arm defined between first and second ends, said  
first crank arm being of a defined length "l<sub>1</sub>" between its two ends, the length  
30 "l<sub>1</sub>" being no greater than the length "L<sub>1</sub>" of the first link; and

first means for mounting each of said first and second ends of the first  
crank arm to pivot freely respectively on the second end of the first link and on  
the base means.

35 Other characteristics and advantages of the present invention appear  
from the following description given with reference to the accompanying  
drawings by way of non-limiting illustration, and in which:

Figure 1 is a theoretical diagram of the device of the invention for protecting and neutralizing a needle for medical use or the like;

Figure 2 is a perspective view of a preferred embodiment of the device of the invention;

Figures 3 to 5 are fragmentary longitudinal section views of the embodiment shown in Figure 2, respectively in three positions in which the device of the invention can be found while it is being used, which positions are respectively referred to in the description below as the "starting position" (Figures 2 and 3), the "in-use position" (Figure 4), and the "locked position" (Figure 5);

Figure 6 is a diagram of an another embodiment of the device of the invention;

Figures 7 and 8 are two orthogonal diagrammatic section views of an another embodiment of the device of the invention, Figure 7 being a section view on line I-I in Figure 8 and Figure 8 being a section view on line II-II in Figure 7;

Figures 9 and 10 are fragmentary views of the device of Figures 7 and 8 shown in two respective configurations, Figure 9 showing a portion of the device in an "intermediate" configuration corresponding to preparing to neutralize the needle, and Figure 10 showing the same portion of the device in its configuration where the needle is completely neutralized, and

Figures 11 and 12 are two embodiments of the base means as illustrated in Figures 1 to 10.

Figure 1 is a theoretical diagram of a device of the invention for protecting and neutralizing a needle 1 for medical use or the like, the needle having a sharp end 2 and a base end 3, it being understood that this theoretical diagram could equally well be a diagrammatical representation of an embodiment of the device.

With reference to the diagram, the device comprises a sleeve 10 having a through bore 11 defined on a given axis 12, said through bore 11 being of a section that is not less than that of the needle to be protected so as to enable the sleeve to slide easily, advantageously over the entire length of the needle 1.

In this embodiment, the device has a link 13 comprising first 15 and second 17 ends, said link having a defined length "L<sub>1</sub>" between its two ends.

This link 13 is associated with a point 39 of the sleeve 10 by first resilient return hinge means 19 which connect the first end 15 of the link 13 to

the sleeve 10, said first hinge means being mounted relative to the link in such a manner as to ensure that the link takes up a defined equilibrium position extending in a direction that makes an acute angle  $\alpha$  relative to the axis 12 of the through bore so that, when the link is moved away from this equilibrium position under drive from any force, it tends automatically to return to said position as soon as the action of the force ceases.

The device also includes base means 21 suitable for receiving the base end 3 of the needle 1. These base means 21 may be of any type. For example, they may be constituted by a conically tapered end fitting, but clearly they can take up any other shape as a function of the nature and the use of the needle. These means can even be constituted by a portion of a syringe or the like.

These means 21 may also be constituted by a sheath or the like suitable for surrounding and engaging the base portion 3 of the needle to be protected 1. This is the embodiment shown in Figures 1 to 5.

In Figure 1, the device also has a crank arm 22 defined between first and second ends 24 and 26. This crank arm 22 is of defined length " $l_1$ " between its two ends 24 and 26, where the length " $l_1$ " is no greater than the length " $L_1$ " of the first link.

As shown diagrammatically in Figure 1, the device finally includes first means 28 for mounting each of the first and second ends 24 and 26 of the crank arm 22 so that they can pivot freely respectively relative to the second end 17 of the link 13 and relative to a point 38 on the base means 21.

The device as described above operates and is used as follows:

Firstly, it is assumed that the device is in the configuration (I) referred to as the "starting position" as shown in Figure 1 in solid lines and as shown in Figures 2 and 3. In this position, the sharp end 2 of the needle is situated inside the through bore 11 made in the sleeve 10 and is thus protected therein.

In practice, the device can be associated with a needle 1 while the device is in this configuration (I), and then the resulting assembly can be sterilized and commercialized in conventional manner, e.g. in a sterile package or blister.

When the needle is to be used by nursing staff, the "protection device and needle" assembly is extracted from the packaging, and then the device is put into the configuration (II) referred to as the "in-use position" as shown in chain-dotted lines in Figure 1 and as shown in Figure 4.



To move the needle protection device from its starting position (I) to its in-use position (II), the user exerts, e.g. by hand, opposing forces on the sleeve 10 and on the base 21 so as to move the sleeve closer to the base, in sliding motion as represented by arrow 35.

5 During this movement, the resilient hinge 19 enables the link 13 initially to be subjected to first pivoting in a clockwise direction, as shown in Figure 1, about the hinge point 39. This movement is imposed by the crank arm 22 pivoting counterclockwise about its free pivot point 30. When its free pivot point 28 passes through and moves below the plane 37 perpendicular to the  
10 axis 12 and containing the above-defined point 38 on the base, the return spring effect of the above-defined hinge 19 tends to cause the link 13 to be subjected to pivoting in the opposite direction, i.e. counterclockwise as shown in Figure 1, thereby returning it towards its original position relative to the axis 12.

15 Under the action of this resilient return force which can be in addition to the opposing forces exerted between the sleeve 10 and the base 21, the link 13 thus drives the sleeve even more rapidly towards the base, and the device takes up its in-use position (II) shown in chain-dotted lines in Figure 1.

In this configuration (II), the needle 1 is completely disengaged. It can  
20 then be used in conventional manner for the function for which it is designed, given that this function need not be described herein since the use of a needle is well known per se.

When the needle has been used, the user can push the sleeve 10 back towards the sharp end 2 of the needle tending to cause it to return to its  
25 starting position, with the sleeve 10 sliding along the needle 1 in the direction of arrow 36 until the sharp end 2 of the needle is situated inside the bore 11 and is covered by the sleeve 10.

The device can be moved manually from its in-use position (II) to its starting position (I) by pressing against the end 24 of the crank arm 22 relative  
30 to the base 21.

It is recalled that Figure 1 is a diagram showing the principle of the device of the invention, and also showing a first embodiment thereof. In this embodiment, the device has only one link 13 and only one crank arm 22, and although it is completely functional, it is nevertheless advantageous to give the  
35 device a structure of the kind shown in Figures 2 to 5.

The embodiment of the device shown in Figures 2 to 5 is advantageous since its structure is symmetrical and thus balanced, thereby improving its operation compared with the operation of the embodiment shown in Figure 1.

In the embodiment shown in Figures 2 to 5, and compared with the embodiment shown in Figure 1, the device of the invention further includes: a second link 14 defined between first and second ends 16 and 18, said second link being of defined length " $L_2$ " between its two ends; second resilient return hinge means 20 for connecting the first end 16 of the second link to the sleeve 10, the second hinge means being organized to cause the second link to take up a defined equilibrium position on a direction that makes an acute angle  $\alpha'$  with the axis of the through bore; a second crank arm 23 defined between first and second ends 25 and 27, the second crank arm being of defined length " $l_2$ " between its two ends, the length " $l_2$ " being no greater than the length " $L_2$ " of the link; and second means 29, 31 for mounting the first and second ends of the second crank arm respectively to pivot freely on the second end of the second link 14 and on the base means 21.

In the advantageous embodiment shown, in order to obtain a device that is accurately symmetrical about the axis 12, the lengths " $L_1$ " and " $L_2$ " are substantially equal to a common value " $L$ " and the lengths " $l_1$ " and " $l_2$ " are substantially equal to a common value " $l$ ".

In addition, in order to make the device easier to manufacture industrially and in order to make it as compact as possible, it is advantageous for the two links 13, 14 and for the two crank arms 22, 23 to lie substantially in the same plane and to form substantially a quadrilateral whose diagonals are substantially perpendicular, the diagonal connecting the vertices of the quadrilateral situated respectively at the sleeve 10 and at the base means 21 substantially coinciding with the axis 12 of the through bore 11.

It is also possible for the same material, e.g. a plastics material, to be used to make at least two of the following elements: sleeve 10; base means 21; link 13, 14; crank arm 22, 23; hinge means 19, 20; and freely pivoting mounting means 28, 29, 30, 31.

Nevertheless, it is particularly advantageous to make all of the component elements of the device out of said same material, thereby enabling it to be made as a single piece by the well known method of molding. Concerning this point, Figures 2 to 5 show, by way of example, the shape which can be given to each of the elements when made of a plastics material

by the molding technique, and they also show reinforcing means for stiffening the links and the crank arms.

This method of manufacture also makes it possible to provide the hinge means 19, 20 and the freely pivoting mounting means 28, 29, 30, 31, directly and simultaneously with the other component elements of the device. In particular, the functions of the resilient return hinge means and of the freely pivoting mounting means can easily be obtained by giving an appropriate shape firstly to the portions of plastics material connecting the links 13, 14 to the sleeve, and secondly to the portions of plastics material connecting the crank arms 22, 23 to the links and to the base means 21.

Making resilient return hinges and freely pivoting hinges in this way by using the characteristics of the material and special shapes such as walls of reduced thickness, or the like, is well known to persons skilled in plastics, and is not described more fully herein.

To stiffen the device as a whole when it is in its starting position prior to first use, it is advantageous for it further to include relatively rigid strut means 40 directly or indirectly interconnecting a link 13 and a crank arm 22.

In Figures 2 and 3, these strut means 40 are shown for the case when the structure of the device is in the form of a quadrilateral. In this embodiment, the strut means 40 are constituted by a bar 41 or the like connected via its two ends to the two crank arms 22 and 24, and having a weak point 42, e.g. in its middle. In this case, the connection between the link 13 and the crank arm 22 is an indirect connection.

Nevertheless, in a configuration other than that shown, the bar 41 can connect a link to a crank arm. The person skilled in the art will select the configuration that is most suitable as a function of the use of the device and/or as a function of its method of manufacture. For example, it is possible to choose an embodiment of the bar 41 that connects the end 15 of the link 13 to the end 26 of the crank arm 22, or a bar that connects the sleeve 10 to the base 21.

In conventional manner, the weak point 42 makes it possible, under the effect of a given amount of force, to break the strut means such as the bar 41 at its weak point. This force can be obtained, e.g. by exerting a force directly on the two portions of the bar situated on either side of its weak point 41, or indirectly by causing the device to go from its starting position (I), Figure 3, to its in-use position (II), Figure 4.

This characteristic is advantageous since, as mentioned above, it makes it possible to stiffen the device while it is in its starting position (I), and also because it serves to inform any user of a needle provided with such a protection device whether there is any risk that the needle has already been used. An intact bar means that it is certain that the needle has not been used, while a broken bar indicates that it might already have been used, in which case, on safety grounds, it would be more prudent not to use it.

As mentioned above, once the needle has been used, it is possible to return the device to its starting position (I), Figure 3, thereby at least hiding the sharp end of the needle. Nevertheless, when using only the structural elements as described above, there is a risk that the sharp end can inadvertently become disengaged again from the inside of the sleeve, and for the needle to be used again, for example.

Thus, it is advantageous for the device of the invention to further include snap-fastening means 50 for directly or indirectly locking the link and the crank arm relative to each other in a given position, in which the sharp end of the needle can no longer move out from inside the sleeve. By way of example, this position is one which enables the device to take up a position (III) or "locking position" as shown in Figure 5 and as represented by dashed lines in Figure 1. In this locking position (III) of the device, the sharp end of the needle is held definitively inside the sleeve, thereby preventing any risk of injury or of reuse.

Figures 2 to 5 show an embodiment of the snap-fastening means 50 for locking the link and the crank arm relative to each other in a given position. These locking means 50 are constituted by two hooks 51 and 52 secured respectively to the two links 13 and 14, and which hook together when, under the action of pressure exerted on the two links, the links are moved to be very close to each other, as shown in Figure 5.

The lengths of the sleeve 10, of the links, and of the crank arms are determined in such a manner that, when the protection device is in this locking position (III), the links and the crank arms are substantially in alignment and the sharp end 2 of the needle 1 lies inside the sleeve 10.

To achieve this result, it is necessary for the length "M" of the sleeve, the length "L" of the link 13 (or of the links 13 and 14), and the length "I" of the crank arm 22 (or of the crank arms 22 and 23) to be determined in such a manner that the sums  $L + I$  and  $L + I + M$  bracket the length "A" of the needle

1 that is to be protected as measured between its sharp end 2 and its base end 3, i.e. these lengths must satisfy the following relationship:

$$L + I < A < L + I + M$$

One embodiment of the locking means 50 is described above, however it is clear that other types can exist, for example pawls or the like positioned on the two curved portions 60 and 61 adjacent to the freely pivoting mounting means 28 and 29, to act respectively between the links 13, 15 and the crank arms 22, 23 and which face one another when the device is in its locked position (III). These pawls are not shown in order to simplify the drawings. For example they may be constituted by two projections situated on the two curved portions 60 and 61 respectively and including, for example, curved ends shaped to pass over each other when the links and the crank arms are brought into alignment, and shaped so as to make it impossible to separate them by moving in the opposite direction.

These snap-fastening locking means may also be constituted by two tamperproof male-female engagement elements, having complementary barbs respectively on their outer walls and on their inner walls, which barbs can move relative to each other only in one direction of displacement of the male element in the female element. Barbs of this type are well known per se to the persons skilled in the art and are therefore not described in greater detail herein.

The figure 6 is a diagram of an another embodiment of the device of the invention.

As shown in Figure 6, the device of the invention for protecting and neutralizing a needle 1 for medical use or the like includes, in addition to the essential characteristics described above with reference to Figures 1 to 5, a casing 70 made of a resilient material surrounding, under tension, the assembly constituted by the sleeve 10, the first and second links 13, 14, the first and second hinge means 19, 20, the first and second crank arms 22, 23, the first and second means 28, 29, 30, 31 for mounting each of the first and second ends of the first and second crank arms respectively on the second ends 17, 18 of the first and second links 13, 14 and on the base means 21, and at least a portion of the base means 21.

The resilient material from which the casing 70 is made is transparent, or substantially transparent, so that users of the device can see through the wall of the casing and therefore see, in particular, the needle and any

indications that may possibly be carried by the various elements mentioned above.

The needle 1 is thus protected from the outside environment, as with a "blister" type casing. However, unlike a prior art blister which must be removed before the needle can be used, the casing 70 does not have to be removed. When the needle moves out from the sleeve as explained above with reference to Figures 1 to 5, it passes through the wall of the casing 70 without difficulty and, as the material from which the casing is made is also resilient, said wall fits tightly around the needle to constitute a sealed passage.

The device may further include a sachet 71 or the like disposed inside the casing 70, said sachet being made of a non-stretch material and containing a given substance.

The sachet is also capable of tearing under a given traction, and means 72, 73 are provided for securing two of its points 74, 75 with two substantially opposite points of the inside wall of the casing 70 that are advantageously situated substantially facing the first and second means 28, 29 for mounting the first ends of the first and second crank arms to pivot freely on the second ends of the first and second links.

By way of example, the substance contained in the sachet 71 presents at least one of the following properties: being suitable for absorbing at least a portion of visible light, being suitable for hardening, being suitable for sterilizing.

In this way, when the needle 1 is used for the first time as explained above, and the two hinges 28, 29 move away from each other when the sleeve descends along the needle, the two points 74, 75 also move away from each other, pulling the sachet and causing it to tear. The substance that it contains thus spreads into the casing 70.

However, the sachet 71 tears only when the sharp end 2 of the needle 1 has already passed through the wall of the casing and is ready to be used for an injection.

It should be noted that the substance spread inside the casing cannot escape therefrom, since, as mentioned above, the wall of the envelope where perforated by the needle fits tightly around the needle and constitutes a sealed passage.

Thus, when the substance is suitable for absorbing at least a portion of visible light, i.e. when it is colored, it is visible to the human eye and, if the

colored substance has filled the chamber of the casing, then the users of the device are informed of the fact that the needle might already have been used.

When the substance is suitable for hardening, once the needle has been used and the entire device has been returned to its original configuration after injection, the links, the crank arms, the sleeve, and the base become embedded in the substance and secured to one another. It is therefore no longer possible to reuse the needle.

Finally, when the substance is suitable for sterilizing objects, once the device has been returned to its original position after the needle has been used, the needle is soaked in the substance that has spread inside the casing and is therefore sterilized by said substance, thereby avoiding contamination if ever a person should be pricked with the sharp end of a needle which has inadvertently come out of the casing. Figures 7 to 10 show another embodiment of the device of the invention for protecting and neutralizing a needle for medical use or the like.

This device, according to the figures 7 and 8, comprises a sleeve 204 with a through bore 205, the through bore having first and second outlets 206 and 207, said through bore being defined on a given axis 208 and being of cross-section that is not less than that of the needle 201 so that the needle can slide through said through bore.

The device also has both a base 209 secured to the base end 203 of the needle 201, said base serving in conventional manner to connect the needle to a syringe, and resilient link means 210 connecting the sleeve 204 to the base 209, these resilient link means enabling the sleeve 204 to slide along the needle 201, with the needle penetrating the through bore 205 of the sleeve via its first outlet 206 so that the sleeve is suitable for taking up two extreme positions: a first position in which the sleeve surrounds the sharp end 202 of the needle, this sharp end being situated at a given distance from the second outlet 207 of the through bore 205; and a second position in which the face 211 of the sleeve 204 that includes the first outlet 206 of the through bore is located close to the base 209.

These resilient link means 210 are constituted, for example, by two links 113 and 114 each having respective first and second ends 115, 116 - 117, 118, said links being of a defined length "L" between their two ends; first resilient return hinge means 119, 120 for connecting the first ends 115, 116 of the two links to the sleeve 204, said first hinge means being organized so that the first two links take up a defined equilibrium position on a direction that

makes an acute angle  $\alpha$  relative to the axis of the through bore ; two crank arms 122, 123, said crank arms being respectively defined between first and second ends 124, 125 - 126, 127 and being of defined length "I" between their two ends, where the length "I" of the crank arms is no greater than the length "L" of the links ; and first means 128, 129, 130, 131 for mounting each of the first and second ends of the two crank arms respectively to pivot freely relative to the second ends 117, 118 of the two links, and relative to the base 221. Advantageously, the two links and the two crank arms are situated substantially in the same plane and form substantially a quadrilateral whose diagonals are substantially perpendicular. In addition, it is advantageous for the length "L" of the links and for the length "I" of the crank arms to be determined in such a manner that the sums  $L + I$  and  $L + I + M$ , where "M" represents the length of the sleeve 204, bracket the length of the needle 201 to be protected as measured between its sharp end 202 and its base end 203.

The device also has both a first channel portion 212 formed in the sleeve 204 and intersecting the through bore 205 in its portion lying between its second outlet 207 and the sharp end 202 of the needle 201 when the sleeve 204 is in its first position, and a shutter 213 slidably mounted in said first channel portion 212, said shutter being suitable for taking up a first position and a second position: the first position being one in which it is not situated in the through bore 205; and the second position being one in which it is situated in the through bore. The device also has means 220 for applying a pressure force on the shutter 213 when the sleeve 204 comes close to the base 209 on the sleeve going from its first position to its second position.

In a preferred embodiment, these means 220 comprise a second channel portion 221 formed in the sleeve 204 in continuity with said first channel portion 212 and opening out via an outlet orifice 222 in the face 211 of the sleeve that includes the first outlet 206 of the through bore 205, associated with a flexible rod 223 that is preformed into an arcuate shape and that is slidably mounted in said second portion of the second channel portion 221. A first end 224 of the two ends of the flexible rod is associated with the shutter 213, while its other end 225 initially emerges from the outlet orifice 222 of the second channel portion by an amount that is not less than the distance which the shutter 213 needs to travel in order to pass from its first position to its second position.

These means 220 also include a release cavity 226 adjacent to the second channel portion 221 and in communication with said second channel



portion, the shape of the release cavity also being defined so that, when the shutter 213 is held in its first position, the flexible rod 223 can deform in bending like a strung bow and can penetrate laterally into said release cavity 226 when the face 211 of the sleeve having said first outlet 206 of the through bore 205 comes close to the base 209.

The device also has means 227 for locking the second end 225 of the flexible rod 223 in position when the rod is retracted into the second channel portion 221. These means 227 are constituted by at least one barb 228 secured to the flexible rod 223 and a housing 229 complementary to the barb 228 formed in the wall of the second channel portion 221 so as to engage the barb in a male-female type manner.

In an advantageous embodiment as shown in the figures, the first channel portion 212 comprises at least first and second parts 231 and 232 disposed on either side of the through bore 205, the first part 231 of the first channel portion being in line with the second channel portion 221, the shutter 213 being contained completely within said first part 231 of the first channel portion 212 when it is in its first position.

The device also includes a substantially U-shaped fork 233 secured to the shutter 213, the two limbs 234 and 235 of the fork being spaced apart from each other by a distance that is not less than the diameter of the needle 201, and said fork 233 being shaped in such a manner that, when the shutter 213 is in its first position, the space 236 defined between the two limbs 234 and 235 lies on the axis 208 of the through bore 205, with the two limbs 234 and 235 extending at least to some extent into the second part 232 of the first channel portion.

In an advantageous embodiment, the flexible rod 223, the shutter 213, and the fork 233 are made as a single piece, e.g. of molded plastics material.

With the above-defined structure, it is advantageous for the axes of the two channel portions 212 and 221 to be contained in a common plane 240 which also contains the axis 208 of the through bore 205. In which case, the sleeve 204 can be made as two half-shells 241 and 242 organized to be assembled together on the plane 240 which contains the channel portions 212 and 221, thus making it possible to use plastics material, for example, to make the sleeve by using the molding technique with molds that are very simple to make. To obtain the device, it suffices to place the single "flexible rod and shutter and fork" piece in the two channel portions and to enclose it by placing

the two half-shells one against the other, after which the half-shells can be bonded together, e.g. by laser beam.

The above-described device as regarding Figures 7 and 8, operates and is used as follows:

5 It is firstly stated that the needle is present in the device in a configuration of the kind shown in Figures 7 and 8.

In this configuration, the shutter 213 is entirely contained in the first part 231 of the first channel portion 212, with the fork 233 allowing the needle 201 to pass through, and with the end 225 of the flexible rod 223 emerging via the  
10 orifice 222 of the second channel portion 221, the sharp end 202 of the needle being properly protected since it is surrounded by the sleeve 204.

When a user seeks to perform an injection using such a needle, the user slides the sleeve 204 towards the base 209. During this movement, the two links 113 and 114 are caused to pivot respectively clockwise and counter-  
15 clockwise while the two crank arms 122 and 123 are caused to pivot respectively counterclockwise and clockwise. The needle comes out from the through bore 205 via its outlet 207, passing between the two limbs 234 and 235 of the fork 233.

When the sleeve 204 comes close to the base 209, the end 225 of the  
20 rod 223 comes into abutment against the base. Since the needle is in position between the two limbs of the fork, the shutter 213 is held in position, and when its end 225 is pushed into the second channel portion 221, the rod 223 folds into an arcuate bow-shape, penetrating into the release cavity 226. When the end 225 is almost fully retracted into the second channel portion 221, the barb  
25 228 catches in the housing 229. At this stage, the device takes up the configuration shown in Figure 9.

After the injection has been completed, the user causes the sleeve 204 to slide back along the needle until it returns to the position shown in Figure 7. Since the end 225 of the prestressed rod 223 is held in place by mutual  
30 engagement between the barb and the housing, the rod applies thrust on the shutter 213. So long as the needle is to be found between the two limbs 234 and 235 of the fork, the shutter remains in its starting position (Figure 9). However, when the sleeve returns to its starting position relative to the base 209, the sharp end 202 of the needle is disengaged from the fork 233 so the  
35 shutter is subjected to drive from the thrust force exerted by the prestressed rod 223, thereby causing the shutter to move into the first channel portion 212 so as to shut off the through bore 205. This translation movement of the

It is then impossible for a user to use the needle 201 again since the user can no longer cause the sleeve to slide towards the base, given that the sharp end of the needle comes automatically into abutment against the shutter 213 which prevents it from moving out of the through bore 205.

In these two embodiments, the base means 21 or 209 comprise two first and second rings 301, 302 (figure 11), 311, 312 (figure 12), with the first ring 301, 311 receiving the low end 3, 203 of the needle, and means 320 for connecting the two rings between them by weakpoints.

In a preferential embodiment, as that which is illustrated on figure 12, the total depth of these two openings when the two rings are connected between them, is lower than the height of end-part 323.

When the base means is carried out as described compared to figure 11 or figure 12, the device according to the invention brings an even greater safety when using the needles of medical use.

In the case of the embodiment of the base means according to figure 12, the end-part 323 can be plugged in force in openings 321, 322 and, to

remove it, it is necessary to exert on it a relatively strong traction which involves a rupture of the weak points and a dissociation of the two rings 311, 312, with the ring 312 remaining plugged in the end-part. The fixing of the second ring 312 on end-part 323 may be reinforced by the presence of the not-withdrawal ring 330 on the wall 331 of this second ring.

5

09674643-14000

## CLAIMS

1/ A device for protecting and neutralizing a needle (1, 201) for medical use or the like, the needle having a sharp end (2, 202) and a base end (3, 203), the device being characterized by the fact that it comprises:

5 a sleeve (10, 204) having a through bore (11, 205) defined on a given axis (12, 208), said through bore being of a section that is not less than that of the needle to be protected;

at least one first link (13, 113, 14, 114) having first and second ends (15, 115, 16, 116, 17, 117, 18, 118), said link being of a length "L<sub>1</sub>" defined  
10 between said two ends;

first resilient return hinge means (19, 20) for connecting the first end (15, 16) of the first link to the sleeve (10), said first hinge means being organized so that said first link takes up a defined equilibrium position on a direction that makes an acute angle (a) with the axis of the through bore;

15 base means (21, 209) suitable for receiving the base end (3, 203) of the needle to be protected (1, 201);

at least one first crank arm (22, 122, 23, 123), said first crank arm being defined between first and second ends (24, 124, 25, 125 - 26, 126, 27, 127), said crank arm being of a length "l<sub>1</sub>" defined between its two ends, the length  
20 "l<sub>1</sub>" of the first crank arm being no greater than the length "L<sub>1</sub>" of the first link; and

first means (28, 128, 29, 129, 30, 130, 31, 131) for mounting each of said first and second ends of the first crank arm to pivot freely respectively on the second end (17, 18) of the first link and on the base means (21, 209).

25 2/ A device according to claim 1, characterized by the fact that it further includes strut means (40) connecting said link (13, 14) to said crank arm (22, 23) when they are in a first given position, said strut means including a weak point (41) making it possible, on application of a given force, to break said strut means at said weak point.

3/ A device according to claim 1 or 2, characterized by the fact that it further includes snap-fastening means (50) to lock said link and said crank arm relative to each other in a second given position (Figure 5).

35 4/ A device according to any one of claims 1 to 3, characterized by the fact that it further includes:

a second link (13, 14) having first and second ends (15, 16 - 17, 18), said second link being of a length " $L_2$ " defined between said two ends;

second resilient return hinge means (19, 20) for connecting the first end (15, 16) of the second link to the sleeve (10), said second hinge means being organized so that said second link takes up a defined equilibrium position on a direction that makes an acute angle ( $\alpha'$ ) with the axis of the through bore;

a second crank arm (22, 23), said second crank arm being defined between first and second ends (24, 25 - 26, 27), said second crank arm being of a length " $l_2$ " defined between its two ends, the length " $l_2$ " of the second crank arm being no greater than the length " $L_2$ " of the second link; and

second means (28-31) for mounting each of said first and second ends of the second crank arm to pivot freely respectively on the second end (13, 14) of the second link and on the base means (21).

5/ A device according to claim 4, characterized by the fact that the lengths " $L_1$ " and " $L_2$ " are substantially equal to a common value " $L$ " and that the lengths " $l_1$ " and " $l_2$ " are substantially equal to a common value " $l$ ".

6/ A device according to claim 4 or 5, characterized by the fact that the first and second links and the first and second crank arms are situated substantially in a common plane and form substantially a quadrilateral whose diagonals are substantially perpendicular, the diagonal interconnecting the vertices of the quadrilateral situated respectively at the sleeve (10) and at the base means (21) coinciding substantially with the axis (12) of the through bore (11).

7/ A device according to any one of claims 1 to 6, characterized by the fact that at least two of the following elements are made of the same material: sleeve (10); base means (21); link (13, 14); crank arm (22, 23); hinge means (19, 20); and freely pivoting mounting means (28, 29, 30, 31).

8/ A device according to claim 7, characterized by the fact that said at least two elements are made by molding.

9/ A device according to claim 8, characterized by the fact that the material is a plastics material.

10/ A device according to any one of claims 1 to 9, characterized by the fact that the length "L<sub>1</sub>" of the link and the length "l<sub>1</sub>" of the crank arm are determined in such a manner that the sum L<sub>1</sub> + l<sub>1</sub> and the sum L<sub>1</sub> + l<sub>1</sub> + M, where "M" represents the length of the sleeve (10), bracket the length "A" of the needle to be protected (1) as measured between its sharp end (2) and its base end (3).

11/ A device according to any one of claims 4 to 10, characterized by the fact that it further includes a casing (70) made of a resilient material surrounding under tension the assembly constituted by the sleeve (10), the first and second links (13, 14), the first and second hinge means (19, 20), the first and second crank arms (22, 23), the first and second means (28-31) for mounting the first and second ends of the first and second crank arms to pivot respectively on the second ends (17, 18) of the first and second links (13, 14) and on the base means (21), and at least a portion of the base means (21).

12/ A device according to claim 11, characterized by the fact that the resilient material from which the casing (70) is made is transparent.

13/ A device according to claim 11 or 12, characterized by the fact that it further includes a sachet (71) made of a non-stretch material, the sachet (71) containing a given substance and being capable of tearing under a given traction, and means (72, 73) for securing the sachet (71) and the casing (70) substantially at two opposite points (74, 75) of the inside wall of the casing (70), the two said points being situated substantially facing the first means (28, 29) for mounting the first ends of the first and second crank arms to pivot freely on the second ends of the first and second links.

14/ A device according to claim 13, characterized by the fact that the substance contained in the sachet (71) presents at least one of the following properties: being suitable for absorbing at least a portion of visible light, being suitable for hardening, being suitable for sterilizing.

15/ A device for protecting and neutralizing a needle (1, 201) for medical use or the like according to any one of claims 1 to 14, the needle having a sharp end (2, 202) and a base end (203), the device comprising:

a sleeve (204) having a through bore (205), said through bore having first and second outlets (206, 207), said through bore being defined on a given axis (208) and having a cross-section that is not less than that of the needle (201), the needle being suitable for sliding through said bore;

a base (209) secured to the base end (203) of the needle (201); and resilient link means (210) connecting the sleeve (204) to the base (209), said resilient link means enabling the sleeve (204) to slide along the needle (201), the needle passing through the bore (205) of the sleeve via the first outlet (206) thereof, said sleeve being suitable for taking up two extreme positions:

- a first position in which the sleeve surrounds the sharp end (202) of the needle, said sharp end being situated at a given distance from the second outlet (207) of the through bore (205); and

- a second position in which the face (211) of the sleeve (204) that includes the first outlet (206) of the through bore is positioned adjacent to the base (209);

the device being characterized by the fact that it further comprises:

a first channel portion (212) made in the sleeve (204) and intersecting the through bore (205) in its portion lying between its second outlet (207) and the sharp end (202) of the needle (201) when the sleeve (204) is in its first position;

a shutter (213) slidably mounted in the first channel portion (212), said shutter being suitable for taking up a first position and a second position, the first position being one in which it is not situated in the through bore (205), and the second position being one in which it is situated in the through bore; and

means (220) for applying thrust on said shutter (213) when the sleeve (204) comes close to the base (209) on passing from its first position to its second position.

16/ A device according to claim 15, characterized by the fact that the means (220) for applying thrust on said shutter when the sleeve comes close to the base on passing from its first position to its second position are constituted by:

a second channel portion (221) made in the sleeve (204) in continuity with the first channel portion (212) and opening out via an outlet orifice (222) in the same face (211) of the sleeve as has the first outlet (206) of the through bore (205);



002011-24347980  
00574643-110210

a flexible rod (223) preformed into an arcuate bow shape and slidably mounted in said second channel portion (221) in such a manner that a first end (224) thereof is associated with the shutter (213), and a second end (225) thereof emerges from the outlet orifice (222) of the second channel portion by an amount that is not less than the distance the shutter (213) needs to travel in order to pass from its first position to its second position; and

a release cavity (226) adjacent the second channel portion (221) and in communication with said second channel portion, the release cavity being designed so that, when the shutter (213) is held in its first position, the flexible rod (223) can deform in bending to penetrate laterally into said release cavity (226) when the face (211) of the sleeve having the first outlet (206) of the through bore (205) comes close to the base (209).

17/ A device according to claim 16, characterized by the fact that it further includes means (227) for locking the position of the second end (225) of the flexible rod (223) when said rod is caused to enter into the second channel portion (221).

18/ A device according to claim 17, characterized by the fact that the means (227) for locking the position of the second end (225) of the flexible rod (223) when it is retracted into the second channel portion (221) are constituted by at least one barb (228) secured to the flexible rod (223) and a housing (229) complementary to the barb (228) formed in the wall of the second channel portion (221).

19/ A device according to any one of claims 15 to 18, characterized by the fact that the first channel portion (212) has at least a first part (231) and a second part (232) formed on either side of the through bore (205), the first part (231) of the first channel portion being in line with the second channel portion (221), the shutter (213) being contained completely within said first part (231) of the first channel portion (212) when it is in its first position, and by the fact that the device further includes a substantially U-shaped fork (233) secured to the shutter (213), the two limbs (234, 235) of the fork being spaced apart from each other by a distance of not less than the diameter of the needle (201), said fork (233) being shaped in such a manner that, when the shutter (213) is in its first position, the gap (236) defined between the two limbs (234, 235) thereof is situated on the axis (208) of the through bore (205) and the two

limbs (234, 235) extend at least in part into the second part (232) of the first channel portion (212).

5 20/ A device according to claim 19, characterized by the fact that the flexible rod (223), the shutter (213), and the fork (233) are made as a single piece.

21/ A device according to claim 20, characterized by the fact that said piece is made of plastics material by molding.

10 22/ A device according to any one of claims 16 to 21, characterized by the fact that the two channel portions (212, 221) are contained in a plane (240) that also contains the axis (208) of the through bore (205), the sleeve (204) being made as two half-shells (241, 242) organized to be assembled together about said plane (40) containing the two channel portions (212, 221).

15 23/ A device according to any one of previous claims, characterized by the fact that the base means (21, 209) comprises two first and second rings (301-302, 311-312), the first ring (301, 331) receiving the low end (3, 203) of the needle, and means (320) for connecting said two rings between them by weak points.

20 24/ A device according to claim 23, characterized by the fact that each of the two rings comprises an opening (321, 322), the two openings being realized to form, when the two rings are connected between them, the female part of a male-female jointing able to cooperate with the complementary male part

25 constituted by an end-part (323) of a syringe (325), the total depth of these two openings when the two rings are connected between them, being lower than the height of end-part of the syringe.

30 25/ A device according to any one of claims 23 and 24, characterized by the fact that it further includes a not-withdrawal ring (330) located on the wall (331) of said second ring.

## ABSTRACT

The invention relates to devices for protecting a needle 1 for medical use or the like and having a sharp end 2 and a base end 3. The device of the invention is essentially characterized by the fact that it comprises a sleeve 10 having a bore 11 on an axis 12 and of section not less than that of the needle to be protected, a link 13 of length " $L_1$ ", resilient return hinge means 19 for connecting one end 15 of the link 14 to the sleeve 10, the link taking up a defined equilibrium position on a direction making an acute angle  $\alpha$  with the axis of the bore 11, base means 21 suitable for receiving the end 3 of the needle 1, a crank arm 22 of length " $K_1$ " no greater than the length " $L_1$ " of the link, and means 28, 30 for mounting each of the first and second ends of the crank arm 22 to pivot freely respectively on the end 17 of the link 13 and on the base means 21.



2/7




fig. 2






fig. 6

5/7




fig. 8




fig. 9







fig. 10





7/7



# Declaration and Power of Attorney for Patent Application

## Déclaration et Pouvoirs pour Demande de Brevet

### French Language Declaration

En tant que l'inventeur nommé ci-après, je déclare par le présent acte que:

Mon domicile, mon adresse postale et ma nationalité sont ceux figurant ci-dessous à côté de mon nom.

Je crois être le premier inventeur original et unique (si un seul nom est mentionné ci-dessous), ou l'un des premiers co-inventeurs originaux (si plusieurs noms sont mentionnés ci-dessous) de l'objet revendiqué, pour lequel une demande de brevet a été déposée concernant l'invention intitulée

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

et dont la description est fournie ci-joint à moins que la case suivante n'ait été cochée:

- ☐ a été déposée le 07 May 1999 sous le numéro de demande des Etats-Unis ou le numéro de demande international PCT FR99/01083 et modifiée le \_\_\_\_\_ (le cas échéant).

Je déclare par le présent acte avoir passé en revue et compris le contenu de la description ci-dessus, revendications comprises, telles que modifiées par toute modification dont il aura été fait référence ci-dessus.

Je reconnais devoir divulguer toute information pertinente à la brevetabilité, comme défini dans le Titre 37, § 1.56 du Code fédéral des réglementations.

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

DEVICE FOR PROTECTING AND  
NEUTRALIZING A NEEDLE FOR MEDICAL  
USE

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

the specification of which is attached hereto unless the following box is checked:

- ☒ was filed on \_\_\_\_\_ as United States Application Number or PCT International Application Number \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

## French Language Declaration

Je revendique par le présent acte avoir la priorité étrangère, en vertu du Titre 35, § 119(a)-(d) ou § 365(b) du Code des Etats-Unis, sur toute demande étrangère de brevet ou certificat d'inventeur ou, en vertu du Titre 35, § 365(a) du même Code, sur toute demande internationale PCT désignant au moins un pays autre que les Etats-Unis et figurant ci-dessous et, en cochant la case, j'ai aussi indiqué ci-dessous toute demande étrangère de brevet, tout certificat d'inventeur ou toute demande internationale PCT ayant une date de dépôt précédant celle de la demande à propos de laquelle une priorité est revendiquée.

Prior foreign application(s)

Demande(s) de brevet antérieure(s)

98/062771 ✓

France ✓

(Number)

(Country)

(Numéro)

(Pays)

98/16701 ✓

France ✓

(Number)

(Country)

(Numéro)

(Pays)

Je revendique par le présent acte tout bénéfice, en vertu du Titre 35, § 119(c) du Code des Etats-Unis, de toute demande de brevet provisoire effectuée aux Etats-Unis et figurant ci-dessous.

(Application No.)

(Filing Date)

(N° de demande)

(Date de dépôt)

(Application No.)

(Filing Date)

(N° de demande)

(Date de dépôt)

Je revendique par le présent acte tout bénéfice, en vertu du Titre 35, § 120 du Code des Etats-Unis, de toute demande de brevet effectuée aux Etats-Unis, ou en vertu du Titre 35, § 365(c) du même Code, de toute demande internationale PCT désignant les Etats-Unis et figurant ci-dessous et, dans la mesure où l'objet de chacune des revendications de cette demande de brevet n'est pas divulgué dans la demande antérieure américaine ou internationale PCT, en vertu des dispositions du premier paragraphe du Titre 35, § 112 du Code des Etats-Unis, je reconnais devoir divulguer toute information pertinente à la brevetabilité, comme défini dans le Titre 37, § 1.56 du Code fédéral des réglementations, dont j'ai pu disposer entre la date de dépôt de la demande antérieure et la date de dépôt de la demande nationale ou internationale PCT de la présente demande:

(Application No.)

(Filing Date)

(N° de demande)

(Date de dépôt)

(Application No.)

(Filing Date)

(N° de demande)

(Date de dépôt)

Je déclare par le présent acte que toute déclaration ci-incluse est, à ma connaissance, véridique et que toute déclaration formulée à partir de renseignements ou de suppositions est tenue pour véridique; et de plus, que toutes ces déclarations ont été formulées en sachant que toute fausse déclaration volontaire ou son équivalent est passible d'une amende ou d'une incarcération, ou des deux, en vertu de la Section 1001 du Titre 18 du Code des Etats-Unis, et que de telles déclarations volontairement fausses risquent de compromettre la validité de la demande de brevet ou du brevet délivré à partir de celle-ci.

I hereby claim foreign priority under Title 35, United States Code, § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below, and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

Droit de priorité non revendiqué

15 May 1998 ✓

(Day/Month/Year Filed)

(Jour/Mois/Année de dépôt)

30 December 1998 ✓

(Day/Month/Year Filed)

(Jour/Mois/Année de dépôt)

I hereby claim the benefit under Title 35, United States Code, § 119(c) of any United States provisional application(s) listed below.

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

(Status)(patented, pending, abandoned)

(Statut)(breveté, en cours d'examen, abandonné)

(Status)(patented, pending, abandoned)

(Statut)(breveté, en cours d'examen, abandonné)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

## French Language Declaration

POUVOIRS: En tant que l'inventeur cité, je désigne par la présente l'(les) avocat(s) et/ou agent(s) suivant(s) pour qu'ils poursuive(nt) la procédure de cette demande de brevet et traite(nt) toute affaire s'y rapportant avec l'Office des brevets et des marques: (mentionner le nom et le numéro d'enregistrement).

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: (list name and registration number)

John H. Mion, Reg. No. 18,879; Donald E. Zinn, Reg. No. 19,046; Thomas J. Macpeak, Reg. No. 19,227; Robert J. Sosa, Jr., Reg. No. 21,020; Darryl Mezin, Reg. No. 22,063; Robert V. Simon, Reg. No. 22,775; Peter D. Olney, Reg. No. 24,513; J. Frank Oels, Reg. No. 24,625; Wadell A. Bignart, Reg. No. 24,861; Robert G. Mohrman, Reg. No. 19,093; Linda Gubinsky, Reg. No. 24,834; Neil B. Siegel, Reg. No. 24,240; David J. Cushing, Reg. No. 25,703; John R. Inge, Reg. No. 26,556; Joseph J. Buck, Jr., Reg. No. 26,472; Sheldon I. Leadenow, Reg. No. 35,400; Richard C. Turner, Reg. No. 29,710; Howard L. Bernstein, Reg. No. 26,665; Alan J. Karpis, Reg. No. 24,426; Kenneth J. Barakat, Reg. No. 31,333; Gordon Kie, Reg. No. 30,764; Susan J. Meek, Reg. No. 35,921; Frank L. Bernatkin, Reg. No. 31,684; Mark Richard, Reg. No. 32,197; William H. Mander, Reg. No. 32,156; Scott M. Daniels, Reg. No. 32,562; Brian W. Hanson, Reg. No. 32,778; Abraham J. Rosner, Reg. No. 33,716; Bruce E. Kramer, Reg. No. 33,725; Paul F. Neils, Reg. No. 33,102; and Bret E. Schweitzer, Reg. No. 33,356.

Adresser toute correspondance à:

Send Correspondence to:

SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC  
2100 Pennsylvania Avenue, N.W., Suite 800  
Washington, D.C. 20037-3202

Adresser tout appel téléphonique à:  
(nom et numéro de téléphone)

Direct Telephone Calls to: 202-293-7060  
(name and telephone number)

Nom complet de l'unique ~~et~~ premier inventeur

Full name of sole or first inventor

Vojin JEREMIJEVIC

Signature de l'inventeur

Date

Inventor's signature

Date

Domicile 12, Avenue des Tilliers  
93100 MONTREUIL-sous-BOIS (FRANCE) FAX

Residence

Nationalité Française

Citizenship

Adresse postale 12, Avenue des Tilliers  
93100 MONTREUIL-sous-BOIS (FRANCE)

Post Office Address

Nom complet du second co-inventeur, le cas échéant

Full name of second joint inventor, if any

Signature du second inventeur

Date

Second inventor's signature

Date

Domicile

Residence

Nationalité

Citizenship

Adresse postale

Post Office Address

(Fournir les mêmes renseignements et la signature de tout co-inventeur supplémentaire.)

(Supply similar information and signature for third and subsequent joint inventors.)

2016-2017

<b>Additional prior foreign applications:</b>			
<b>Number (Numéro)</b>	<b>Country (Pays)</b>	<b>Day/Month/Year Filed (Jour/Mois/Année de dépôt)</b>	<b>Priority Not Claimed (Droit de priorité non revendiqué)</b>
99/01284	France -	4 February 1999 ✓	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
<b>Additional provisional applications:</b>			
<b>Application Number (N° de demande)</b>		<b>Filing Date (Date de dépôt)</b>	
<b>Additional U.S. applications:</b>			
<b>Application Number (N° de demande)</b>	<b>Filing Date (Date de dépôt)</b>	<b>Status (patented, pending, abandoned) (Statut (breveté, en cours d'examen, abandonné))</b>	